



SK350 MINI SKID STEER

MINI SKID STEERS



SK350 MINI SKID STEER

1

Highly responsive steering with little or no vibration feedback, increasing operator comfort and productivity.

2

Auxiliary valve contains a float section for better performance of attachments that follow the contour of the ground.

3

Quick-disconnect manifold for simple and efficient changing of hydraulic attachments.

6

Exterior-mounted gas and hydraulic tanks for easy refueling without raising the hood; 7.5-gallon (30.3-L) fuel tank provides up to five hours of operation.

5

Stand-on platform keeps you out of mud and debris and reduces fatigue.





4

Greater lift and dump heights than the competition, so it can dump into vehicles that others can't, increasing its versatility.



At less than 36 inches wide, the **Ditch Witch® SK350 Mini Skid Steer** can go just about anywhere you need it to. But with twice the hydraulic flow of other machines its size, it does the same work as much larger machines. Powered by a 20-hp (14.9-kW) Kohler® engine, the SK350 can drive more than 70 quick-change attachments, giving you the versatility you need. And whatever the job is, you'll operate from a comfortable stand-on platform.

WE'RE IN THIS TOGETHER.





SK350 ATTACHMENTS

The Ditch Witch® organization offers a full line of quick-change attachments compatible with the SK350 Mini Skid Steer. Visit the SK350 product page on ditchwitch.com to use our interactive attachment selector, or ask your Ditch Witch dealer about additional attachment options.

SK350 MINI SKID STEER SPECIFICATIONS

	U.S.	METRIC
DIMENSIONS		
Overall height	42.5 in	1.1 m
Overall length	58.2 in	1.5 m
Width, excluding tracks	32 in	813 mm
Weight	1,660 lb	753 kg
Hinge pin height, max	70.4 in	1.8 m
Wheelbase/track length	30 in	762 mm
Track width, max	35.1 in	892 mm
Ground clearance		
Center	4 in	101 mm
Side	2.5 in	64 mm
Tipping capacity	1,030 lb	467 kg
Rated operating capacity		
35% of tipping capacity	350 lb	158 kg
Angle of departure	18°	

POWER		
Engine	Kohler® CH20	
Fuel	Gasoline	
Cooling medium	Air	
Number of cylinders	2	
Displacement	38 in ³	624 cm ³
Bore	3.03 in	77 mm
Stroke	2.64 in	67 mm
Gross power, installed net power per SAE J1349 @ 3,600 rpm	20 hp	14.9 kW
Rated speed	3,600 rpm	

OPERATION		
Ground drive speed		
Forward/reverse	3 mph	4.8 km/h
Ground pressure		
7-in (180-mm) tracks	4 psi	0.28 bar

HYDRAULIC SYSTEM

	U.S.	METRIC
Auxiliary: gear pump	12 gpm	45.4 l/min
Pressure	2,300 psi	158 bar
Ground drive: dual hydrostat		
Flow rate	11 gpm	42 l/min
Pressure	2,330 psi	162 bar

FLUID CAPACITIES

Fuel tank	7.5 gal	30.3 L
Engine oil	2 qt	1.9 L
Hydraulic reservoir	7 gal	26.5 L

BATTERY

SAE reserve capacity rating	41 min
SAE cold crank rating @ 0°F (-18°C)	340 amps
Electrical system	12V

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.