

# SK755 MINI SKID STEER

 **Ditch Witch**<sup>®</sup>



**MINI SKID STEERS**

# SK755 MINI SKID STEER

1

Two-way auxiliary control foot pedal helps you maintain hydraulic flow to the attachment with the pedal, freeing your hands to control depth and ground speed.

2

Float section on the lift arm control valve enhances the productivity of attachments that follow the contour of the ground.

3

Ergonomic controls and 4.7-mph (7.6-km/h) ground drive speed enhance jobsite efficiency and productivity.

9

Innovative high-drive track system has bolt-on sprockets and wide track rollers for greater stability, longer track life and easy maintenance.

8

Low-maintenance track-tensioning system features a grease cylinder for easy adjustment and track removal, for increased track life and reduced downtime.

7

Efficient, low-maintenance Kubota® diesel engine provides outstanding power for all machine functions.



4

Auxiliary hydraulics with quick-connect attachment fittings, so you can perform multiple jobs on the same jobsite in less time.

5

800-lb (363-kg) rated operating capacity and an 81-inch (206-m) hinge-pin height for more productive loading.



The Ditch Witch® SK755 Mini Skid Steer is built to outperform on any jobsite. Featuring a high-drive track system and an enhanced operator's station, it delivers superior performance through increased ground clearance, more lift capacity, faster ground speed, longer track life, and more operator comfort. And with more horsepower to the attachment than the competition, the SK755 will help make you more productive and more profitable, job after job.

WE'RE IN THIS TOGETHER.

6

Industry-leading power to the attachment provides unbeatable productivity; accepts more than 70 attachments for a wide range of utility, landscaping, plumbing, and other underground construction tasks.





### SK755 ATTACHMENTS

The Ditch Witch® organization offers a full line of quick-change attachments compatible with the SK755 Mini Skid Steer. Visit the SK755 product page on [ditchwitch.com](http://ditchwitch.com) to use our interactive attachment selector, or ask your Ditch Witch dealer about additional attachment options.

## SK755 MINI SKID STEER SPECIFICATIONS

	U.S.	METRIC
<b>DIMENSIONS (STD)</b>		
Operating height, max. std. bucket	103 in	2.62 m
Overall length of machine, std. bucket	105 in	2.67 m
Overall length of loader, no attachment	86 in	2.19 m
Machine weight (no attachment, fluids full)	2,890 lb	1314 kg
Hinge pin height, max	81 in	2.06 m
Wheelbase/track length	43 in	1.09 m
Track width		
Max	42 in	1.06 m
Min	36 in	0.91 m
Ground clearance		
Center	8.9 in	226 mm
Side	3.7 in	94 mm
Tipping capacity	2,285 lb	1039 kg
Rated operating capacity		
35% of tipping capacity	800 lb	363 kg
Angle of departure	27°	
<b>POWER</b>		
Engine	Kubota® D1105-T	
Fuel	Diesel	
Number of cylinders	3	
Displacement	68.5 in <sup>3</sup>	1.12 L
Bore	3.07 in	78 mm
Stroke	3.09 in	78.4 mm
Rated speed	3,000 rpm	
Gross power rating	32.8 hp	24.5 kW
Emissions compliance	EPA Tier 4i	EU Stage IIIA

	U.S.	METRIC
<b>OPERATION</b>		
Ground drive speed		
Forward/reverse	4.7 mph	7.6 km/h
Ground pressure* (ISO/CD 16754)		
7-in (180-mm) tracks	4.8 psi	0.33 bar
9-in (230-mm) tracks	3.8 psi	0.26 bar
<b>HYDRAULIC SYSTEM</b>		
Auxiliary circuit		
Double gear pump		
Flow rate (Pump #1)	8.5 gpm	30 l/min
Flow rate (Pump #2)	5.5 gpm	21 l/min
Pressure	3,000 psi	207 bar
Ground drive		
Dual hydrostatic pumps		
Flow rate	13.9 gpm	52 l/min
Pressure	3,500 psi	241 bar
<b>FLUID CAPACITIES</b>		
Fuel tank capacity	10.5 gal	40 L
Engine oil, w/filter	4.2 qt	4 L
Hydraulic reservoir capacity	9.2 gal	35 L
<b>BATTERY</b>		
SAE reserve capacity rating	110 min	
SAE cold crank @ 0°F (-18°C)	800 amps	
Electrical system	12V	

\* Includes machine weight, 175 lb (80 kg) bucket, and 165 lb (75 kg) operator.

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.